

newline



newline **C SERIES**

65"

75"

86"


AN IDEAL SOLUTION FOR THE **INTELLIGENT CLASSROOM**

SIMPLIFY LEARNING AMPLIFY CONNECTION

Experience the simplicity and efficiency of the Newline C Series for your classrooms and teams. This interactive display features a 4K LED display, embedded speakers, and various connectivity options. Experience innovative paper-like writing technology, supporting up to 40 points of touch and write, all wrapped in a user-friendly and intuitive design.

The Newline C series effortlessly connects to all your devices through USB-C or other input ports, empowering educators to conduct dynamic and interactive lessons without the hassle of extensive training.

The installation and setup are a breeze, requiring minimal IT support, while user maintenance costs have been streamlined for maximum efficiency. Elevate your educational and collaborative experiences with the Newline C Series – where simplicity meets innovation.



Zero
Bonding




40 Points



4K HD



178°
View Angle



Speaker



Palm Rejection

newline C *SERIES*

Model Name	TT-6523C	TT-7523C	TT-8623C
	Display Specifications		
Active Screen Size	65"	75"	86"
Screen Type	LCD (Direct LED Backlight)		
Resolution	3840 × 2160 (4K)		
Display Area	1429 x 804 mm	1651 x 929 mm	1896 x 1066 mm
Display Ratio	16:9		
Display Color Depth	1.07 Billion		
Brightness	400 cd/m²		
Contrast Ratio	Typ. 4000:1		
Response Time	8ms		
Viewing Angle	178°		
LCD Refresh Rate	60Hz		
Life Time	≥ 50,000 hours		
	Touch		
Touch Surface Technology	Anti-Glare		
Transparency	88% ± 3		
Surface Hardness	8H		
Touch Sensor	IR		
Touch Points	Windows 40 Points		
Touch Screen Writing Tools	Stylus or Finger		
	Connectivity		
USB Data Ports	1*USB Type-C		
	2*Type-B (Touch)		
	2*USB 3.0 Type-A + 1*USB 2.0 Type-A Embedded + 2*USB 2.0 Type-A For Signal		
Digital Audio-Video Inputs	3*HDMI 2.0 + 1*VGA + 1*VGA-Audio		
	1*Microphone In		
Digital Audio-Video Outputs	1*Audio Line out		
	1*S/PDIF Out		
Integrated PC Slot	Available		
Control Input	1*RS-232		
Network	1*IN & 1*OUT RJ-45 connector		
	Embedded Operating System		
CPU	Arm Cortex-A55 x 4		
GPU	Arm Mali-G52 MC1		
RAM	2GB		
ROM	8GB		
External Memory	N/A		
Operating System	No OS		
	Power		
Working Voltage	AC100-240V Max. 4.4A	AC100-240V Max. 4.95A	AC100-240V Max. 5.5A
Max Power Consumption	302W	343W	415W
Standby Power Consumption	< 0.5W	< 0.5W	< 0.5W
	Speaker		
Position	Bottom Front		
Rated Impedance	6Ω		
Frequency Response	200Hz - 20KHz when SPL is -10dB		
Output S.P.L.	79+3dB		
Max Power Output	15W × 2		
	Transportation/ Storage		
Storage Temperature / Humidity	-20~60°C / 0~90%RH (non-condensing)		
Working Temperature / Humidity	0°C - 40°C / 20% - 80% RH (Non-Condensing)		
Mounting (Optional)	Wall-Mounted / Mobile Stand		
Outline Dimensions	1513 x 923 x 110 mm	1735 x 1048 x 111 mm	1981 x 1186 x 111 mm
Packing Dimensions	1640 x 185 x 1030 mm	1859 x 205 x 1160 mm	2119 x 228 x 1290 mm
Net Weight	38.5 kg	50 kg	74 kg
Gross Weight	40 kg	63 kg	80 kg

newline

HEADQUARTERS (TX,USA)
TEL: +1 888 233 0868
info@newline-interactive.com

EUROPE OFFICE
TEL: +34 911169178
info_eu@newline-interactive.com

ASIA PACIFIC OFFICE
TEL: +886 3 550 4768
info_ap@newline-interactive.com

KOREA OFFICE
TEL: +82 2 2638 5140
koreainfo@newline-interactive.com

INDIA OFFICE
TEL: 1 800 419 0309
info.in@newline-interactive.com